



2MP 25x IR PTZ IP Camera

1920x1080, 25x Optical Zoom

PRODUCT SPEC SHEET
R2-2MPIRPTZ



The R2-2MPIRPTZ is a 2MP (1920x1080) PTZ camera constructed with a 25x module and provides HD image quality.

For additional monitoring and cloud capabilities, integrate with Capture Cloud (powered by Eagle Eye), and connect to Capture Remote Monitoring.*

FEATURES

- 1/2.8" PROGRESSIVE SCAN CMOS
- 25x OPTICAL ZOOM, 16x DIGITAL ZOOM
- 2MP (1920x1080) @25/30FPS
- SUPPORTS FACE, HUMAN AND VEHICLE DETECTION AND CAPTURE
- SUPPORTS SMOKE AND FIRE DETECTION, SMART MOTION DETECTION
- AUTO TRACKING AND PERIMETER PROTECTION BASED ON DEEP LEARNING
- WDR, 3D DNR, ICR, HLC, BLC, DEFOG, ANTI-SHAKE
- SMART IR DISTANCE UP TO 150M (492.1 FT)
- IP66 RATED
- WARRANTY: 36 MONTHS
- PART #: R2-2MPIRPTZ
- UPC: 840049308404
- DIMENSIONS: Ø6.82" × 11.52"
- WEIGHT: 7.72 LB



FOR MORE INFORMATION, CONTACT YOUR ADI SALES PERSON.

CATEGORY

IMAGE SENSOR	1/2.8" PROGRESSIVE SCAN CMOS
MAX. RESOLUTION	1080P (1920x1080)
ELECTRONIC SHUTTER	AUTO/MANUAL, 1/5 ~ 1/20,000S
MIN. ILLUMINATION	COLOR: 0.05 LUX @ (F1.6, AGC ON) B/W: 0.005 LUX @ (F1.6, AGC ON), 0 LUX WITH IR
DAY & NIGHT	AUTO (ICR)
IR DISTANCE	SMART IR, UP TO 150M (492.1 FT)
IR ON/OFF CONTROL	AUTO/MANUAL

LENS

FOCAL LENGTH	5 ~ 125MM
MAX. APERTURE	F1.6 ~ F3.67
ANGLE OF VIEW	H: 57.02° ~ 3.36°, V: 33.14° ~ 1.91°
OPTICAL ZOOM	25x
DIGITAL ZOOM	16x
FOCUS CONTROL	AUTO/MANUAL/SEMI-AUTOMATIC

PTZ

PAN/TILT RANGE	PAN: 0° ~ 360° ENDLESS TILT: -10° ~ +90°
MANUAL CONTROL SPEED	PAN: 0.1° ~ 180°/S, TILT: 0.1° ~ 90°/S
PRESET SPEED	PAN: 180°/S, TILT: 90°/S
PRESETS	400
PTZ MODE	6 TRACK, 12 SCAN, 12 TOUR (UP TO 32 PRESETS PER TOUR)
3D POSITIONING	SUPPORTED
POWER-OFF MEMORY	SUPPORTED

PTZ STATUS DISPLAY

SUPPORTED

IDLE MOTION

THE TIME CAN BE SET (1-240 MINUTES), AND FUNCTIONS SUCH AS PRESET POSITIONS, PATROLS, SCANS AND TRACKS CAN BE RUN.

VIDEO
STREAMING CAPABILITY

3 STREAMS

STREAM/FRAME RATE

STREAM1: 1920x1080, 1280x720 @ 25/30FPS
STREAM2: D1, VGA, 640x360, CIF, QVGA @ 25/30FPS
STREAM3: VGA, CIF, QVGA @ 25/30FPS

BIT RATE CONTROL

CBR/VBR

BIT RATE

STREAM1: 200KBPS-12MBPS
STREAM2: 100KBPS-6MBPS
STREAM3: 100KBPS-3MBPS

SMART ENCODER

SUPPORTED

REGION OF INTEREST (ROI)

SUPPORTED

IMAGE
IMAGE ADJUSTMENT

BRIGHTNESS, SHARPNESS, CONTRAST, SATURATION ADJUSTABLE

MIRROR

SUPPORTED

EXPOSURE MODE

AUTO/MANUAL

WHITE BALANCE

AUTO/MANUAL

DAY/NIGHT SETTING

AUTO, DAY, NIGHT, TIME

SMART IR

SUPPORTED

NOISE REDUCTION

2D/3D DNR

WIDE DYNAMIC RANGE

TRUE WDR

IMAGE ENHANCE-MENT

HLC, BLC, DEFOG, ANTI-SHAKE

S/N RATIO

55DB

MOTION DETECTION

SUPPORTED

**FOR MORE INFORMATION,
CONTACT YOUR ADI SALES PERSON.**

PRIVACY MASKING	SUPPORTED
AUDIO	
COMPRESSION	G.711 (8KBPS), RAW_PCM (16KBPS)
SMART FUNCTIONS	
MULTI-OBJECT DETECTION	SUPPORTS FACE, HUMAN , VEHICLE DETECTION AND CAPTURE
INTELLIGENT ANALYSIS	INTRUSION, SINGLE LINE CROSSING, DOUBLE LINE CROSSING, LOITERING, WRONG WAY, ILLEGAL PARKING (SUPPORTS ACCURATE DETECTION OF HUMANS AND VEHICLES)
SMOKE AND FIRE DETECTION	SUPPORTED
PEOPLE COUNTING	SUPPORTED
SMART MOTION DETECTION	SUPPORTED
SMART TRACKING	SUPPORTED
NETWORK	
PROTOCOLS	IPV4, IPV6, TCP / IP, HTTP, HTTPS, UPNP, RTSP / RTP / RTCP, IGMP / MULTICAST, SMTP, DHCP, NTP, DNS, DDNS, QOS, SNMP, 802.1X, UDP, ICMP, ARP, TLS
INTEROPERABILITY	ONVIF, SDK, CGI
STREAMING METHOD	UNICAST
MAX. USER ACCESS	10 USERS
WEB VIEWER	<IE11, CHROME, FIREFOX, MICROSOFT EDGE
LANGUAGE	ENGLISH, CHINESE, POLISH, ITALIAN, PORTUGUESE, SPANISH, RUSSIAN, FRENCH, CZECH, HUNGARIAN. DEFAULT: ENGLISH
INTERFACE	
NETWORK INTERFACE	1 X RJ45, 10/100 MBPS SELF-ADAPTIVE ETHERNET PORT
AUDIO INTERFACE	1CH INPUT, 1CH OUTPUT
ALARM INTERFACE	2CH INPUT, 2CH OUTPUT

SD CARD SLOT	YES (BUILT-IN), UP TO 256GB
ELECTRICAL	
POWER SUPPLY	AC24V/DC36V/POE+ (IEEE 802.3AT) STANDARD EQUIPPED: DC36V
POWER CONSUMPTION	LESS THAN 30W
OPERATING TEMPERATURE	-40°C ~ 60°C (-40°F ~ 14°F)
OPERATING HUMIDITY	LESS THAN 90% RH
INGRESS PROTECTION	IP66, TVS4000V
CERTIFICATIONS	CE/FCC
CASING	METAL
DIMENSIONS	ø173.2 × 292.6MM (ø6.82 × 11.52 INCHES)
NET WEIGHT	3.5KG (7.72 LB)

**FOR MORE INFORMATION,
CONTACT YOUR ADI SALES PERSON.**